



WELDING & CUTTING MACHINES

306-309 ARC Welding 317-318 Induction Heaters and Plasma Cutter 310-313 MIG Welding 318-324 Welding Accessories

TIG Welding

314-316

INDUSTRIAL AND WORKSHOP WELDING

DID YOU KNOW?

The Draper Expert range of welding machines is designed and manufactured with the highest quality components, guaranteeing durability. Aimed at the semi-professional/professional user, the Draper Expert welding range is backed by our comprehensive warranty and after-sales service.

The Draper range of welding machines is designed for general workshop welding tasks and is backed by our comprehensive warranty and after-sales service.

ARC WELDING MACHINES

The running order of the arc welding machines starts at the highest amperage (250A) through to the lowest (100A).

Page **306**



MIG WELDING MACHINES

The running order of the MIG welding machines starts at the highest amperage (250A) through to the lowest (100A) and features both gas and gasless machines.

Page **309**



TIG WELDERS, INDUCTION HEATERS, PLASMA CUTTERS



WELDING CONSUMABLES AND ACCESSORIES

We stock a wide selection of quality accessories and consumables, from MIG wire, electrodes and welding helmets to torches and torch tips.













MMA Inverter Welder with TIG-Lift Dti, 200A

- VRD functionARC forceHot start

- Anti-stickThermal overload protection

| Hototurt | |
|---|--------------------------|
| Amperage range | 20-200A |
| Power supply | 230V |
| Plug Fitted: | NO (32A PLUG REQUIRED) |
| Duty cycle: | 60% @ 200A / 100% @ 160A |
| Dimensions: | 340 x 135 x 235mm |
| Weight (net): | 5.3kg |
| Fan Cooled: | YES |
| Hot Start: | YES |
| Anti-Stick: | YES |
| Euro Torch Connector/Dinse Type Coupling: | 35/50 |
| Arc Force: | YES |
| VRD Function: | YES |
| DTI: | YES |
| TIG-Lift: | YES |
| | |



| Stock | Part | |
|-------|--------|--|
| No. | No. | |
| 70011 | AW200A | |

2

MMA Inverter Welder, 180A

ARC force

- · Fan cooled
- Hot start • Thermal overload protection
- · Anti-stick

| Amperage range: | 20-180A |
|---|-------------------------|
| Power supply: | 230V |
| Plug Fitted: | NO (32A PLUG REQUIRED) |
| Duty cycle: | 60% @ 180A / 100% @140A |
| Dimensions: | 288 x 119 x 207mm |
| Weight (net): | 5.3kg |
| Carry Handle for Portability: | YES |
| Fan Cooled: | YES |
| Hot Start: | YES |
| Anti-Stick: | YES |
| Euro Torch Connector/Dinse Type Coupling: | 10/25 |
| Arc Force: | YES |



| Stock No. | Part No. | |
|--------------|-------------|--|
| 70029 | INV180A | |

3

MMA Inverter Welder, 160A

ARC force

- Fan cooled
- Thermal overload protection
- Hot startAnti-stick

| * Allu-Stick | |
|---|------------------------|
| Amperage range: | 20-160A |
| Power supply: | 230V |
| Plug Fitted: | NO (32A PLUG REQUIRED) |
| Duty cycle: | 60% @160A / 100% @125A |
| Dimensions: | 288 x 119 x 207mm |
| Weight (net): | 5.2kg |
| Carry Handle for Portability: | YES |
| Fan Cooled: | YES |
| Hot Start: | YES |
| Anti-Stick: | YES |
| Euro Torch Connector/Dinse Type Coupling: | 10/25 |
| Arc Force: | YES |



| Stock No. | Part No. | |
|--------------|-------------|--|
| 70030 | INV160A | |



Draper Storm Force® MMA Inverter Welder, 140A

Hot start Anti-stick Portable

Fan cooledThermal overload protection

| Amperage range: | | 20-140A |
|-----------------|-----------------|------------------------|
| Power supply: | | 230V |
| Plug Fitted: | | NO (16A PLUG REQUIRED) |
| Duty cycle: | | 35% @140A / 100% @90A |
| Dimensions: | | 200 x 95 x 145mm |
| Weight (net): | | 3.1kg |
| Carry Handle f | or Portability: | YES |
| Fan Cooled: | | YES |
| Hot Start: | | YES |
| Anti-Stick: | | YES |
| DINSE type: | | 10/25 |
| Stock No. | Part No. | |
| 70041 | INV140A/SF | |

Draper Storm Force® MMA Inverter Welder, 120A • Hot start • Anti-stick • Fan cooled • Thermal overload protection

Anti-stickPortable

| Portable | | |
|------------------------------|----------------|------------------------------------|
| Amperage range | e: | 20-120A |
| Power supply: | | 230V |
| Plug Fitted: | | NO (16A PLUG REQUIRED) |
| Duty cycle: | | 35% @120A / 60% @100A / 100% @ 85A |
| Dimensions: | | 200 x 95 x 145mm |
| Weight (net): | | 3kg |
| Carry Handle fo | r Portability: | YES |
| Fan Cooled: | | YES |
| Hot Start: | | YES |
| Anti-Stick: | | YES |
| DINSE type: | | 10/25 |
| Stock No. | Part No. | |
| 70042 | INV120A/SF | |

STORM FORCE



STORN/ FORCE



ARC Welding section 6



ARC Welder, 180A

- · Stepless current adjustment
- 1.6-4mm electrodes
- Portable

1

- · Fan cooled
- · Thermal overload protection

Amperage range: 70-180A 230V Power supply: Plug Fitted: NO (16A PLUG REQUIRED) Duty cycle: 10% @180A / 60% @73A 345 x 180 x 280mm Dimensions: Weight (net): 17.5kg Stepless Current Adjustment: YES Carry Handle for Portability: YES YES Fan Cooled: Thermal overload protection: YES Stock No. Part No.



- · Stepless current adjustment
- 2.0-3.2mm electrodes
- Portable
- Fan cooled
- · Thermal overload protection

| Amperage range: | | 50-130 <i>A</i> |
|-----------------|------------------|---------------------------------|
| Power supply | : | 230\ |
| Plug Fitted: | | NO (16A PLUG REQUIRED |
| Duty cycle: | | 10% @130A / 40% @65A / 60% @53A |
| Dimensions | | 430 x 230 x 300mm |
| Weight (net): | | 11.5kg |
| Stepless Curr | ent Adjustment: | YES |
| Carry Handle | for Portability: | YES |
| Fan Cooled: | | YES |
| Thermal over | load protection: | YES |
| Stock No. | Part No. | |
| 53084 | AW135T | |
| | | |



ARC Welder, 160A

- · Stepless current adjustment
- 1.6-4mm electrodes
- Portable

2

- · Fan cooled
- · Thermal overload protection

| mormar overreda proteotion | |
|-------------------------------|---------------------------------|
| Amperage range: | 60-160A |
| Power supply: | 230V |
| Plug Fitted: | NO (16A PLUG REQUIRED) |
| Duty cycle: | 10% @160A / 40% @80A / 60% @65A |
| Dimensions: | 430 x 230 x 300mm |
| Weight (net): | 16kg |
| Stepless Current Adjustment: | YES |
| Carry Handle for Portability: | YES |
| Fan Cooled: | YES |
| Thermal overload protection: | YES |
| Stock Part | |



230V Turbo Arc Welder (100A)

- Featuring automatic thermal protection
- Continuous regulation of welding current
- Fitted with an internal cooling fan
- Direct fit earth clamp and electrode holder Supplied with face mask and chipping hammer/wire brush

| | 470 x 270 x 320mm |
|-----------|-------------------|
| | 10% 100A |
| | 1.6mm - 3.2mm |
| | 16A |
| je Range: | 40 - 100A |
| | Single 230V |
| | 15kg |
| Part | |
| AW105T | |
| | No. |



1 NEW

Welding Electrodes, 2.5mm (5kg Pack)

General purpose welding electrodes made from mild steel. Suitable for welding in all positions. They are E6013 rutile electrodes, which can be used with AC and DC currents. Supplied as a 5kg pack, approximately 290 electrodes.

| Stock No. | Part No. | Size | |
|--------------|-------------|-------|--|
| 98441 | WR25A/5KG | 2.5mm | |

2 NEW

Welding Electrodes, 3.2mm (5kg Pack)

General purpose welding electrodes made from mild steel. Suitable for welding in all positions. They are E6013 rutile electrodes, which can be used with AC and DC currents. Supplied as a 5kg pack, approximately 176 electrodes.

| VR32A/5KG | 3.2mm |
|-----------|-----------|
| | VR32A/5KG |

3 NEW

Welding Electrodes, 4.0mm (5kg Pack)

General purpose welding electrodes made from mild steel. Suitable for welding in all positions. They are E6013 rutile electrodes, which can be used with AC and DC currents. Supplied as a 5kg pack, approximately 144 electrodes.

| Stock No. | Part No. | Size | |
|--------------|-------------|-------|--|
| 98443 | WR40A/5KG | 4.0mm | |

4

Welding electrodes

General purpose welding electrodes made from mild steel. Suitable for welding in all positions. They are E6013 rutile electrodes, which can be used with AC and DC currents.

| Stock | Part | Size |
|-------|-------|-------|
| No. | No. | Size |
| 70435 | WR20A | 2.0mm |
| 70436 | WR25A | 2.5mm |
| 70/27 | WD22A | 2 2mm |





Twist-Grip Electrode Holders

For holding electrodes to maximise their usage. Twist-Grip handle grips and releases electrode. Maximum load 400A. 5mm jaw opening. Packed in polybag with display header.

| Stock No. | Part No. | Colour | |
|--------------|-------------|--------|--|
| 08372 | ARCEL02 | Yellow | |

230V MMA to Mig Converter (200A)

- Enables a MMA welder to perform Mig welding
- Achieves both gas and gasless Mig welding
 Uses 0.8mm wires which are housed in the MIG spool gun Supplied with Dinse adaptors and the cables required for converting

| Working Volt | tage: | 33V - 85V |
|---------------|--------------|-------------------|
| Control Volta | age: | 24V |
| Output ampe | erage range: | 35 - 200A |
| Duty cycle: | | 20% 200A |
| Dimensions: | | 195 x 155 x 115mm |
| Weight: | | 3.72kg |
| Stock | Part | |
| No. | No. | |
| 00587 | MCB200 | |

Gas/Gasless MIG Welder, 250A

- Accepts 15kg spoolFull size gas bottle support
- Variable wire speed control
- Thermal overload protection

| Amperage range: | | 40-250A |
|-----------------------|-------------------------|------------------------------|
| Power supply: | | 230V - 32A, 400V - 32A |
| Welding wire spools | size: | 5-15kg |
| Duty cycle 230V: | | 10% 165A, 30% 95A, 60% 65A |
| Duty cycle 400V: | | 10% 250A, 30% 155A, 60% 100A |
| Dimensions: | | 770 x 375 x 530mm |
| Weight (net): | | 58kg |
| Euro Torch Connect | or/Dinse Type Coupling: | 35/50 |
| Compatible with Re | gular gas Bottle: | YES |
| Plug Fitted: | | NO |
| Stock No. 71094 | Part No. MW260T | |



2

Gas/Gasless MIG Welder, 220A

- · Accepts 15kg spool
- · Full size gas bottle support
- Variable wire speed control
 Thermal overload protection

| Titotitian of ottoala protoculoti | |
|-------------------------------------|-----------------------------|
| Amperage range: | 40-220A |
| Power supply: | 230V, 400V |
| Plug Fitted: | NO (16A PLUG REQUIRED) |
| Welding wire spool size: | 5-15kg |
| Duty cycle 230V: | 10% 160A, 30% 90A, 60% 65A |
| Duty cycle 400V: | 10% 220A, 30% 130A, 60% 90A |
| Dimensions: | 770 x 375 x 530mm |
| Weight (net): | 56kg |
| Euro Torch Connector/Dinse Type Co | oupling: 35/50 |
| Compatible with Regular gas Bottle: | YES |
| Stock Part | |
| No. No. | |
| 71093 MW230T | |



3

Gas/Gasless MIG Welder, 180A

- · Accepts 15kg spool

- Full size gas bottle support
 Variable wire speed control
 Thermal overload protection

| mormal overload proteotion | |
|-------------------------------------|----------------------------------|
| Amperage range: | 40-180A |
| Power supply: | 230V |
| Plug Fitted: | NO (16A PLUG REQUIRED) |
| Welding wire spool size: | 5-15kg |
| Duty cycle: | 10% @140A / 30% @80A / 60% @ 55A |
| Dimensions: | 770 x 375 x 530mm |
| Weight (net): | 55kg |
| Euro Torch Connector/Dinse Type Cou | upling: 10/25 |
| Compatible with Regular gas Bottle: | YES |
| Stock Part | |
| No. No. | |
| 71092 MW190T | |





1

Gas/Gasless MIG Inverter Multi-Welder, 200A

- · IGBT Inverter technology
- Digital displayMulti-process welder
- · Gas/Gasless
- Thermal overload protection

| -200A (MIG), 20-180A (MMA) 230V NO (32A PLUG REQUIRED) |
|--|
| |
| NO (32A PLUG REQUIRED) |
| |
| 1.6-5.0mm |
| 5kg |
| 60% @200A / 100% @160A |
| 435 x 220 x 320mm |
| 16.1kg |
| YES |
| 35/50 |
| YES |
| YES |
| YES |
| YES |
| |



3

Gas/Gasless MIG Inverter Multi-Welder Dti, 160A

- IGBT Inverter technology
- · Synergic wire feed
- · Multi-process welder
- Digital displayLatest digital technology for superior performance and precision control

| A | |
|---|------------------------|
| Amperage range: | 20-160A |
| Power supply: | 230V |
| Plug Fitted: | NO (16A PLUG REQUIRED) |
| Electrode size: | 1.6-4.0mm |
| Welding wire spool size: | 1kg and 5kg |
| Duty cycle: | 60% @160A / 100% @120A |
| Dimensions: | 420 x 205 x 300mm |
| Weight (net): | 12kg |
| IGBT Tech: | YES |
| Euro Torch Connector/Dinse Type Coupling: | 10/25 |
| Synergic Wire Feed: | YES |
| Compatible with Regular gas Bottle: | YES |
| Suitable for MMA welding: | YES |
| TIG-Lift: | YES |
| DTi: | YES |
| Stock Part No. No. | |
| 70047 MW160A | |



2

Gas/Gasless AC/DC MIG Aluminium Welder Dti, 160A

- IGBT Inverter technology
- Synergic wire feedGas/Gasless
- Multi-process welderPulse welding

| Puise weiu | ilig | |
|--------------------------------|-------------------------------|------------------------|
| Amperage ra | nge: | 20-160A |
| Power supply | <i>i</i> : | 230V |
| Plug Fitted: | | NO (32A PLUG REQUIRED) |
| Electrode siz | e: | 1.6-4.0mm |
| Welding wire | spool size: | 1kg and 5kg |
| Duty cycle: | | 60% @160A / 100% @120A |
| Dimensions: | | 425 x 220 x 320mm |
| Weight (net): | | 14kg |
| IGBT Tech: | | YES |
| Euro Torch C | onnector/Dinse Type Coupling: | 35/50 |
| Synergic Wir | e Feed: | YES |
| Compatible v | vith Regular gas Bottle: | YES |
| Suitable for N | MMA welding: | YES |
| TIG-Lift: | | YES |
| Alu Only: | | YES |
| Pulse Weldin | g: | YES |
| Digital Displa | ay: | YES |
| DTi: | | YES |
| Stock | Part | The second second |



4

70048

Gasless MIG Inverter Multi-Welder Dti, 120A

- IGBT Inverter technology

- Latest digital technology for superior performance and precision control
- · Thermal overload protection

Synergic wire feed
MIG FCW/MMA Amperage range: 20-120A (MMA), 30-120A (MIG FCW) Power supply: 230V Plug Fitted: NO (16A PLUG REQUIRED) Electrode size: 1.6-3.2mm Welding wire spool size: Duty cycle: 60% @120A / 100% @92A Dimensions: 335 x 135 x 250mm Weight (net): 6.8kg IGBT Tech: YES Euro Torch Connector/Dinse Type Coupling: 10/25 Synergic Wire Feed: YES Suitable for MMA welding: YES DTi: YES Stock Part No. 70049 MW120A



STORM FORCE

Draper Storm Force® Gasless MIG Welder, 150A

- Variable wire speed control
 Ready to weld accessories included
 Fan cooled

- Thermal overload protection

| e: | 80-150A |
|--------------------------|------------------------|
| | 230V |
| | NO (16A PLUG REQUIRED) |
| ool size: | 0.45kg |
| | 10% @150A / 60% @80A |
| | 340 x 345 x 190mm |
| | 17kg |
| Part No. MW150A/SF | |
| | ool size: Part No. |

Gas/Gasless MIG Welder, 160A

- Variable wire speed control

1

- 1kg wire spool included
 Fan cooled
 Thermal overload protection
- · Transport wheels

| 60-160A |
|------------------------|
| 230V |
| NO (16A PLUG REQUIRED) |
| 1kg |
| 10% @160A |
| 510 x 390 x 430mm |
| 32kg |
| YES |
| |
| |





Draper Storm Force® Gasless MIG Welder, 120A • Variable wire speed control

- Ready to weld accessories included
 Fan cooled
 Thermal overload protection

 Carloss

- Gasless

| Amperage range: | | 50-120A |
|-----------------------|--------------------------|----------------------|
| Power supply | <i>y</i> : | 230V |
| Plug Fitted: | | Yes (13A Fitted) |
| Welding wire | spool size: | 0.45kg |
| Duty cycle: | | 10% @120A / 60% @50A |
| Dimensions: | | 340 x 345 x 190mm |
| Weight (net): | | 16kg |
| Stock No. 70051 | Part No. MW120A/SF | |
| 70001 | IVIVV 12UA/3F | |

| Stock No. | Part No. | |
|--------------|-------------|--|
| 63669 | MIG100 | |



Mild Steel MIG Welding Wire

Made from copper coated mild steel. For welding mild and medium tensile steels for impact toughness down to -20°C. Suitable for use with most MIG welders.


| Stock No. | Part No. | Diameter | Weight |
|--------------|-------------|----------|--------|
| 29103 | WMIGMS06700 | 0.6mm | 700g |
| 77175 | WSIF556 | 0.6mm | 5.0kg |
| 29107 | WMIGMS0615 | 0.6mm | 15.0kg |
| 29291 | WMIGMS08700 | 0.8mm | 700g |
| 29292 | WMIGMS085 | 0.8mm | 5.0kg |
| 29528 | WMIGMS0815 | 0.8mm | 15.0kg |
| 29780 | WMIGMS1015 | 1.0mm | 15.0kg |



Aluminium 5356 MIG Welding Wire

Made from aluminium alloy with 5% silicon. 0.8mm wire supplied as a spool. For welding duralumin, cast and wrought alloys. Suitable for use with most MIG welders.

| Stock No. | Part No. | Diameter | Weight |
|--------------|-------------|----------|--------|
| 70085 | WMIGA082000 | 0.8mm | 2kg |
| 30424 | WMIGA08500 | 0.8mm | 500g |



3 Flux Cored MIG Welding Wire

Made from mild steel. Flux cored 0.8mm gasless wire supplied as a spool. Low alloy self-shielding wire. Suitable for use with most MIG welders.

| Stock No. | Part No. | Diameter | Weight | |
|--------------|--------------|----------|--------|--|
| 30644 | WMIGFC08450 | 0.8mm | 450g | |
| 70084 | WMIGFC085000 | 0.8mm | 5.0kg | |



3m MIG Welding Torch

MIG welding torch with direct fit Euro connector. Rubber head mouldings for greater heat resistance. Comfortable grip and heat resistant 3m cable.

| Stock | Part | |
|-------|-----------|--|
| No. | No. | |
| 70088 | WTRCHFURO | |



5 MB15 MIG Torch Tips, 1.0mm (Pack of 5)

Contact tips for use with MB15 MIG welding torches. Manufactured from high conductivity copper alloy. Pack of 5.

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 98458 | PW1/5 | |



0.8mm MB15 MIG Torch Tips (Pack of 5)

Contact tips for use with MB15 MIG welding torches. Manufactured from high conductivity copper alloy. Pack of 5

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 98456 | W608P | |



7

0.6mm MB15 MIG Torch Tips (Pack of 5)

Contact tips for use with MB15 MIG welding torches. Manufactured from high conductivity copper alloy. Pack of 5.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 98454 | W607P/5 | |



8

MIG Welding Tips and Shrouds (Pack of 2)

Contact tips for use with torches supplied with Draper welding machines and other professional MIG welding torches. Shrouds for use with Draper MIG welding torches, packed two per display card.

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 33886 | W577P | |



TIG Welding section 6







1

High Frequency AC/DC TIG/MMA Aluminium Welder Dti, 200A

- IGBT Inverter technology
- High frequency start
 Pulse function

- Foot pedal supplied
 Latest digital technology for superior performance and precision control

| Pulse function | | performance and precision control |
|------------------------------------|---------------------------|-----------------------------------|
| Amperage range: | | 10-200A |
| Power supply: | | 230V-32A |
| Electrode size: | | 1.6-5.0mm |
| Duty cycle: | | 20% @200A / 100% @155A |
| Dimensions: | | 557 x 210 x 395mm |
| Weight (net): | | 25.5kg |
| IGBT Tech: | | YES |
| Euro Torch Conne | ector/Dinse Type Coupling | 35/50 |
| High Frequency S | Start: | YES |
| Suitable for MMA | welding: | YES |
| Foot Pedal: | | YES |
| Suitable for Weld | ing Aluminium: | YES |
| Pulse Welding: | | YES |
| DTi: | | YES |
| Digital Display: | | YES |
| Plug Fitted: | | NO |
| Stock No. | Part No. | |
| 70052 | TW250A | |





3

3-in-1 Multi-Process Welder, 200A

IGBT Inverter technologyMIG/MMA/TIG

· MIG torch, TIG torch and electrode

- holder included
- · Synergic wire feed
- Gas/gasless

| | | 3 |
|-------------------|--------------------------------|----------------------------------|
| Amperage range | : 40-200A (MIG | s), 20-200A (TIG), 30-180A (MMA) |
| Power supply: | | 230V-16A |
| MMA Electrode s | iize: | 1.5-4.0mm |
| MIG Wire size: | | 0.6-0.8mm |
| Flux core wire: | | 0.6-0.8mm |
| Duty cycle MIG: | 30% @ 200A / 100% @150A, | TIG 60% @200A / 100% @150A |
| Duty cycle MMA: | | 35% @180A / 100% @140A |
| Dimensions: | | 460 x 270 x 286mm |
| Weight (net): | | 16.6kg |
| IGBT Tech: | | YES |
| Euro Torch Conn | ector/Dinse Type Coupling: | 10/25 |
| Includes MIG & T | IG Torches & Electrode Holder: | YES |
| IGBT Inverter Tec | chnology: | YES |
| Stock No. | Part No. | |
| 00588 | MPW200 | |

3-in-1 Multi-Process Welder Dti, 200A

- IGBT Inverter technology
- MIG/MMA/TIG
- MIG torch, TIG torch and electrode
- holder included
- Synergic wire feedDigital display

| Amperage range: | 30-200A (MIG), 20-200A (MMA), 20-200A (TIG) |
|----------------------------------|---|
| Power supply: | 230V |
| Plug Fitted: | NO (32A PLUG REQUIRED) |
| MMA Electrode size: | 1.6-5.0mm |
| MIG Wire size: | 0.6-1.2mm |
| Flux core wire: | 0.6-1.2mm |
| Duty cycle: | 60% @200A / 100% @160A |
| Dimensions: | 420 x 205 x 300mm |
| Weight (net): | 13.7kg |
| IGBT Tech: | YES |
| Euro Torch Connector/Dinse Type | Coupling: 10/25 |
| Includes MIG & TIG Torches & Ele | ctrode Holder: YES |
| IGBT Inverter Technology: | YES |
| Anti-Spatter Feature: | YES |
| DTi: | YES |
| Digital Display: | YES |
| Stock Part | |



4

TIG/MMA Welder, 145A

- · IGBT Inverter technology
- 1.6-3.2mm electrodes Portable

- Smooth stable arc
- · Thermal overload protection

| • Pullable | |
|---|-----------------------------|
| Amperage range: | 5-145A (TIG), 20-120A (MMA) |
| Power supply: | 230V |
| Plug Fitted: | NO (16A PLUG REQUIRED) |
| Electrode size: | 1.6-3.2mm |
| Duty cycle: | 60% @145A / 100% @112A |
| Dimensions: | 350 x 132 x 280mm |
| Weight (net): | 7.5kg |
| IGBT Tech: | YES |
| Euro Torch Connector/Dinse Type Coupling: | 10/25 |
| Suitable for MMA welding: | YES |
| Plug Fitted: | NO |
| Stock Part No. No. | |
| 70057 TW145A | |



Air Cooled TIG Welding Torch, 4m, Dinse Type 35-50

TIG welding torch with 35-50 dinse type plug and 3/8" BSP fitting. Lightweight, durable and air cooled with rubber head mouldings for greater heat resistance. 4m cable. Suitable for TIG welding up to 250A. Supplied with accessory pack including 1.6mm collet, 1.6mm collet body and 10mm (No.6) ceramic.

Contents:

- 1 x 1.6mm collet
- 1 x 1.6mm collet body
- 1 x 10mm (No.6) ceramic

| Stock No. | Part No. | Description | |
|--------------|----------------|---------------|---|
| 70087 | WTRCHTIG/35-50 | Welding Torch | |
| | | 3 | _ |



Accessories for Draper TIG Welding Torches

For use with all Draper Inverter/Welder TIG Torches. Packed in polybags.

| Stock No. | Part No. | Description | |
|--------------|-------------|-------------------|--|
| 57552 | W629 | 1.6mm Collet Body | |
| 57551 | W628 | 1.6mm Collet | |



TIG Welding Torch, Dinse Type 10-25mm²

TIG welding torch with 10/25 Dinse type plug and gas 3/8in BSP fitting. For use with all Draper inverter/welders. Lightweight, durable and air cooled with 4M cable and rubber head mouldings for greater heat resistance. Includes accessory pack. Suitable for TIG welding up to 160A.

Contents:

- 1 x TIG torch with 4M cable and 10/25 Dinse type plug and gas 3/8in BSP fitting
- 1 x Accessory pack including 1.6mm collet, 1.6mm collet body, No. 6 ceramic

| Stock No. | Part No. | |
|--------------|-------------|--|
| 57096 | W623 | |



2m TIG Torch Extension Hose with 3/8" BSP

2m extension hose with 3/8 BSP connector. For use with TIG torches and compatible with Stock No. 57096 and 70087. Allows the use of TIG torch with welders offering TIG lift, such as Stock No. 70011, 70048, 70047 and 70043.

| Stock No. | Part No. | Description | |
|--------------|--------------|----------------|--|
| 37774 | WTRCHTIG/EXT | Extension Hose | |



5

200A Earth Clamp and Lead Kit

For use with all Draper Inverter/Welders. 2.5M 16mm welding cable with trailing dinse-type plug and 200A crocodile earth clamp fitted. Packed in polythene bag.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 14448 | W3550 | |



Ceramic Shroud No.6, (Pack of 5)

Durable No. 6 ceramic shrouds. Suitable for use with TIG welding torches. Pack

| Stock No. | Part No. | |
|--------------|-------------|--|
| 98452 | W630B/5 | |





Ceriated Tungsten Electrodes, 1.6 x 150mm (Pack of 10)

Durable 2% ceriated tungsten electrodes 1.6mm x 150mm. Fine grain structure and annealing helps make them resistant to splitting and weld contamination. Suitable for AD and DC currents and ferrous/non-ferrous welding. Thorium free. Pack of 10.

| Stock | Part | |
|-------|---------|--|
| No. | No. | |
| 98447 | W632/10 | |



2

Thoriated Tungsten Electrodes, 1.6 x 150mm (Pack of 10)

Durable 2% thoriated tungsten electrodes 1.6mm x 150mm. Fine grain structure and annealing helps make them resistant to splitting and weld contamination. Suitable for DC currents and ferrous welding. Thorium free. Pack of 10.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 98448 | W639/10 | |



Zirconiated Tungsten Electrodes, 1.6 x 150mm (Pack of 10)

Durable 0.9% zirconiated tungsten electrodes 1.6mm x 150mm. Fine grain structure and annealing helps make them resistant to splitting and weld contamination. Suitable for AC currents and aluminium welding. Pack of 10.

| Stock | Part | |
|-------|---------|--|
| No. | NO. | |
| 98449 | W630/10 | |





Ceriated Tungsten Electrodes, 2.4 x 150mm (Pack of 10)

Durable 2% ceriated tungsten electrodes 2.4 x 150mm. Fine grain structure and annealing make them resistant to splitting and weld contamination. Suitable for AC and DC currents, and both ferrous and non-ferrous welding. Thorium free. Pack of 10.

| Stock | Part | |
|-------|-------------|--|
| No. | No. | |
| 15811 | W632/10/2.4 | |



5 NEW

Thoriated Tungsten Electrodes, 2.4 x 150mm (Pack of 10)

Durable 2% thoriated tungsten electrodes 2.4 x 150mm. Fine grain structure and annealing make them resistant to splitting and weld contamination. Suitable for DC currents and ferrous welding. Pack of 10

| Stock | Part | |
|-------|-------------|--|
| No. | No. | |
| 15861 | W639/10/2.4 | |



6 NEW

Zirconiated Tungsten Electrodes, 2.4 x 150mm (Pack of 10)

Durable 0.9% zirconiated tungsten electrodes 2.4 x 150mm. Fine grain structure and annealing make them resistant to splitting and weld contamination. Suitable for AC currents and aluminium welding. Pack of 10.

| Stock | Part | |
|-------|-------------|--|
| No. | No. | |
| 15933 | W630/10/2.4 | |



TIG Welders Gloves

Pair of grey premium quality welding gloves. Manufactured from goat skin with cow hide cuff. Extra-long cuff (150mm). Reinforced wrist patch and gusseted fingers reduces abrasion and ensures dexterity. Glide patch eases movement and protects the side of the hand when dragging a welding gun. Fully lined with protective material. Reinforced palm and thumb with double Kevlar stitching ensures safety and comfort. Conforms to BS EN388, BS EN407, BS EN12477 and BS EN 420. Size 10.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 70451 | TIGG | |



Induction Heaters & Plasma Cutters





Liquid Cooled Induction Heater, 3.5kW

- Expert Quality
 High powered, 3.5kW liquid cooled induction heater, ideal for industrial applications
- Multi-functions, 3 heating modes, computer controlled
- Fan assisted cooling technology enables continuous use
- Adjustable input and output

power for use in low amperage environments

- Dynamic power adjustments deliver
- maximum efficiency and speed

 Fully adjustable and controllable for maximum versatility
- Universal remote-control program allows linking to external analogue and digital production processes

| Input power: | | 3.5kW |
|--|--|---|
| Operating freque | ency: | 20 - 60kHz |
| Voltage supply: | | 230V 50/60Hz |
| Max current: | | 16A |
| Output power: | | 3kW (16A supply) |
| Liquid tank: | | 1.5L |
| Dimensions: | | 430 x 200 x 200mm |
| Weight: | | 14.6kg approx. |
| Stock No. | Part No. | Description |
| 76171 01062 12042 12041 12040 12039 | IHT-30 AIHT AIHT4 AIHT3 AIHT2 AIHT1 | Induction Heater Coolant (3L) Focus Coil-Straight Focus Coil-Iside Focus Coil-Inclined Focus Coil-Straight With Extender |









Induction Heating Tool Kit, 1.75kW

- Expert Quality
- · Easy to use induction heater, operated by simply installing the appropriate coil type and place over or around the ferrous metal you wish to heat
- · Each kit is supplied with a hardwearing carry case and four

different shaped coils, delivering flexibility of use

Compared against braziers or welding/heating techniques, induction heaters are far safer and economic, as they don't use a naked flame and you save on gas bottle hire

| Input Voltage: | 230V |
|----------------|------------------|
| Power: | 1750W |
| Frequency: | 50/60Hz |
| Weight: | 5.14kg |
| Dimensions: | 200 x 140 x 75mm |

| Stock No. | Part No. | Description |
|----------------|------------------------|-----------------------|
| 80808 | IHT-15 | Induction Heating Kit |
| 80903 80906 | IHT-15/FC IHT-15/PC | Flex Coil Pad Coil |
| 83161 | IHT-15/PC | 15mm Direct Coil |
| 83167 | IHT-15/15MMSC | 15mm Side Coil |
| 80901 | IHT-15/19MMDC | 19mm Direct Coil |
| 83173 | IHT-15/19MMSC | 19mm Side Coil |
| 83162 | IHT-15/20MMDC | 20mm Direct Coil |
| 83168 | IHT-15/20MMSC | 20mm Side Coil |
| 83163 | IHT-15/23MMDC | 23mm Direct Coil |
| 83169 | IHT-15/23MMSC | 23mm Side Coil |
| 80902 | IHT-15/26MMDC | 26mm Direct Coil |
| 83174 | IHT-15/26MMSC | 26mm Side Coil |
| 83164 | IHT-15/32MMDC | 32mm Direct Coil |
| 83170 | IHT-15/32MMSC | 32mm Side Coil |
| 83165 | IHT-15/38MMDC | 38mm Direct Coil |
| 83171 | IHT-15/38MMSC | 38mm Side Coil |
| 83166 | IHT-15/45MMDC | 45mm Direct Coil |
| 83172 | IHT-15/45MMSC | 45mm Side Coil |
| | | |





3

High Frequency Plasma Cutter, 60A

- IGBT Inverter technology
- Integrated gas regulator
- 15mm cut thicknessThermal overload protection

| High frequency pilot arc start | |
|--|------------------------|
| Amperage range: | 20-60A |
| Power supply: | 230V |
| Plug Fitted: | NO (32A PLUG REQUIRED) |
| Max. cutting thickness: | 15mm |
| PSI: | 72.5psi |
| Duty cycle: | 60% @60A 100% @40A |
| Dimensions: | 530 x 210 x 390mm |
| Weight (net): | 17.2kg |
| IGBT Inverter Technology: | YES |
| Integrated Gas Regulator: | YES |
| High Frequency Pilot arc Start: | YES |
| Thermal overload protection: | YES |
| Digital Display: | YES |
| Stock Part No. No. | |
| 70058 IPC60 | |

High Frequency Plasma Cutter, 40A

- IGBT Inverter technology
- · Integrated gas regulator
- · Thermal overload protection

· 12mm cut thickness

| High frequency pilot arc start | mormal eventual protection |
|---------------------------------|----------------------------|
| Amperage range: | 20-40A |
| Power supply: | 230V |
| Plug Fitted: | NO (32A PLUG REQUIRED) |
| Max. cutting thickness: | 12mm |
| PSI: | 72.5psi |
| Duty cycle: | 60% @40A / 100% @25A |
| Dimensions: | 426 x 160 x 285mm |
| Weight (net): | 9.4kg |
| IGBT Inverter Technology: | YES |
| Integrated Gas Regulator: | YES |
| High Frequency Pilot arc Start: | YES |
| Thermal overload protection: | YES |
| Stock Part No. No. | |
| 70066 IPC40 | |



- IGBT Inverter technology
- Integrated gas regulatorBuilt-in water trap
- 8mm cut thickness
- · Thermal overload protection

| Amperage range: | 10-25A |
|------------------------------|-------------------------------|
| Power supply: | 230V |
| Plug Fitted: | Yes (32A Plug Fitted) |
| Max. cutting thickness: | 8mm |
| PSI: | 60psi |
| Duty cycle: | 25% @25A/ 60% @18A/ 100% @13A |
| Dimensions: | 426 x 160 x 285mm |
| Weight (net): | 8.9kg |
| IGBT Inverter Technology: | Yes |
| Integrated Gas Regulator: | Yes |
| Built-in Water Trap: | Yes |
| Thermal overload protection: | Yes |
| Stock Part No. No. | |
| 92454 IPC25 | |



2 NEW

3-Tier Welding Trolley, 50kg

This heavy-duty all-metal welding cart has three shelves for organising welding equipment and accessories. It can transport ARC and MIG welders and plasma cutters up to 440 x 257mm and a standard/large sized industrial gas bottle, secured using the 750mm fitted chain. It is designed for durability and made of thick steel with a black powder-coated finish. There are two large 125mm rear wheels and heavy-duty swivel castors at the front for easy manoeuvrability. Maximum capacity is 50kg.

| OLOOK | | |
|-------|-----|--|
| No. | No. | |
| 08005 | WT | |







240mm Self Grip Sheet Metal Clamp

Manufactured from good quality steel, nickel plated, with quick release lever. Display carton.

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 14027 | 9010S | |



Manufactured from good quality steel, nickel plated, with quick release lever. Display carton.

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 81642 | 9020S | |



Self Grip Welding Clamp, 225mm

Manufactured from good quality steel, nickel plated, with quick release lever. Display carton.

| Stock No. | Part No. | Length | |
|--------------|-------------|--------|--|
| 81650 | 9000S | 225mm | |



Self Grip Welding Clamp Kit (3 Piece)

Manufactured from good quality steel, nickel plated, with quick release lever. Display carton.

Contents:

4

- 1 x 250mm Sheet metal clamp
- 1 x 225mm Welding clamp
- 1 x 280mm C clamp

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 33836 | 9013K | |





5

210mm Soft Grip MIG 'Helper' Pliers

Aids MIG welding including removal of spatter from in and around the shroud, drawing out and cutting off wire and removing contact tips and shrouds. Spring loaded jaws with soft grip handles. Display packed.

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 31489 | WP2 | |



Multi-Purpose Magnetic Holder

For holding workpieces whilst soldering or welding. Working angles: 30°, 45°, 60°, 75°, 90° and 135°. Manufactured from high quality pressed and enamelled steel with strong magnet. Display packed.

| Stock No. | Part No. | Dimensions | |
|--------------|-------------|----------------|--|
| 24577 | WM-1B | 95 x 13 x 65mm | |



Multi-Purpose Magnetic Holder

For holding workpieces whilst soldering or welding. Working angles: 45°, 75° and 135°. Manufactured from high quality pressed and enamelled steel with strong magnet. Display packed.

| Stock No. | Part No. | Dimensions |
|--------------|-------------|------------------|
| 82329 | WM-2/B | 158 x 12 x 102mm |



Multi-Purpose Magnetic Holder

For holding workpieces whilst soldering or welding. Working angles: 45°, 75° and 135°. Manufactured from high quality pressed and enamelled steel with strong magnet. Display packed.

| Stock No. | Part No. | Dimensions | |
|--------------|-------------|-----------------|--|
| 82330 | WM-3/B | 118 x 13 x 82mm | |



Welders Hammer

Hardened and tempered head with steel spring impact resistant handle. Sold loose.

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 45236 | WH/L | |





General Purpose Wire Brush, 250mm

Wire brush designed primarily for cleaning metal prior to welding or removing slag after a weld has been made as well as other brushing applications. The 0.35mm diameter brassed steel wire fill is securely held in a heavy duty spine with polypropylene handle. Display packed.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 20594 | 4863 | |

1 NEW

Anti Spatter Spray, 300ml

Water-based anti spatter aerosol spray. Contains no silicones or solvents. Non-toxic and non-flammable. Designed to prolong tip and shroud life and prevent adhesion of weld spatter to your work area. Does not interfere with the welding process.



| Stock | Part | |
|-------|---------------|--|
| No. | No. | |
| 70452 | ANTISPATTER12 | |



4 NEW

Filter for use with Welding Helmet - Stock No. 02512

Replacement filter for use with Auto-Darkening Multi-Use Welding Helmet – Stock No. 02512.

| Stock | Part | |
|-------|------------|--|
| No. | No. | |
| 04889 | AWHVS-BK-F | |



2 NEW

Draper Expert Air-Fed PAPR Auto-Darkening Welding Helmet, Black

- Electronically controlled airflow with three levels (150L/min, 180L/min and 220L/min)
- · Dual mode airflow adjustment
- Alarm for low airflow and low battery
- · Fire retardant air hose and P3 filter

| Suitability: | | TIG, MIG, arc and grinding |
|--------------|-------------|--------------------------------|
| Airflow rate | es: 150 | L/min, 180L/min and 220L/min |
| Lens size: | | 98 x 48mm |
| Shade leve | ls: | 4 and 9-13 |
| Lens switch | ing time: | 1/25,000s |
| ARC sensor | s: | 2 |
| Operating t | emperatur | e: -10 to +55° |
| Power supp | ıly: | Li-ion battery and solar |
| Battery: | | 12V 4.3Ah Li-ion (replaceable) |
| Weight: | | 2.31kg |
| Stock No. | Part No. | |
| 02518 | WHAFVS | |





3 NEW

Draper Expert Auto-Darkening Multi-Use Welding Helmet

- · Auto switches on striking arc
- Shade coverage includes 4, 5-9 and 9-13
- Solar powered
- · Variable sensivity and dark to light delay (stepless)
- Adjustable headband

Suitability: TIG, MIG, ARC, grinding and plasma cutting

| Lens size: | | 100 x 67mm |
|------------------|----------|-----------------------------|
| Shade levels: | | 4, 5–9 and 9–13 |
| Lens switching | time: | 1/10,000s |
| ARC sensors: | | 4 |
| Sensitivity cont | rol: | Rotary dial |
| Operating temp | erature: | -5 to +55° |
| Power supply: | | Li-ion battery and solar |
| Battery: | | 600mAh Li-ion (replaceable) |
| Weight: | | 522g |
| Stock | Part | |
| No. | No. | |
| 02512 | WHVS | -BK |
| | | |



5 NEW

Outside PC Lens for use with Welding Helmet - Stock No. 02512

Replacement outside PC lens for use with Auto-Darkening Multi-Use Welding Helmet Stock No. 02512. Lens size - H 138 x W 122 x D 1mm

| Stock | Part |
|-------|-------------|
| No. | No. |
| 04897 | AWHVS-BK-LO |



7 NEW

Auto-Darkening Welding Helmet, Red Flames

- Adjustable shade 9-13
- Auto switches on striking arc
- Solar powered
- Suitable for TIG, MIG and arc welding, plasma cutting and also grinding
- Adjustable headband

| Stock No. | Part No. | |
|--------------|-------------|--|
| 02513 | WHVS-RF | |

6 NEW

Inside PC Lens for use with Welding Helmet - Stock No. 02512

Replacement inside PC lens for use with Auto-Darkening Multi-Use Welding Helmet Stock No. 02512. Lens size - H 103.5 x W 72.6 x 1mm

| Stock No. | Part No. | |
|--------------|------------------|--|
| 04808 | Λ\Λ/H\/\$-BK-I I | |



8 NEW

Auto-Darkening Welding Helmet, Blue Skull

- Adjustable shade 9-13
- Auto switches on striking arc
- · Solar powered
- Suitable for TIG, MIG and arc welding, plasma cutting and also grinding
- Adjustable headband

| Stock No. | Part No. | |
|--------------|-------------|--|
| 02514 | WHVS-BS | |

9 NEW

Auto-Darkening Welding Helmet, Playing Cards

- Adjustable shade 9-13
- Auto switches on striking arc
- · Solar powered
- Suitable for TIG, MIG and arc welding, plasma cutting and also grinding
- Adjustable headband

| - Majastas | ic iicaabaiia | |
|--------------|-------------------|---------------------------|
| Suitability: | TIG, MIG, arc, gr | inding and plasma cutting |
| Lens size: | | 92.5 x 42.5mm |
| Shade leve | ls: | 4 and 9-13 |
| Lens switch | ning time: | 3/10,000s |
| ARC senso | rs: | 2 |
| Sensitivity | control: | Rotary dial |
| Operating | temperature: | -5 to +55° |
| Power supp | oly: | Li-ion battery and solar |
| Battery: | Li-ion CR2 | 450 600mAh (replaceable) |
| Weight: | | 440g |
| Stock No. | Part No. | |
| 02515 | WHVS-PC | |



1

Solar Powered Auto-Varioshade Welding and Grinding Helmet

EN175 and BS EN 6100-6-3 and BS EN 6100-6-1

- · Provides instant eye protection
- Large view screen (110 x 90mm)
- · Fitted with grinding mode
- External sensitivity control
- High performance screen filters
- · Protects against UV and IR
- Adjustable headband
- Suitable for all kinds of welding types, including ARC, MIG and low amperage TIG

| erage rio | | |
|---------------------------|--|--|
| 110 x 90mm | | |
| Fully automatic | | |
| AAA battery + solar panel | | |
| rk: 0.02ms | | |
| ht: 0.04ms | | |
| DIN 4 | | |
| nts: DIN 9 - 13 | | |
| 2 | | |
| up to DIN 16 | | |
| -5C - +55C | | |
| 480g | | |
| | | |
| | | |
| | | |





STORM FORCE

2 NEW

Draper Storm Force® Fixed Shade Auto Darkening Welding Helmet

- · Shade 11 welding helmet
- · Auto switches on striking arc
- · Solar powered
- · Adjustable headband

| Welding: | | TIG, MIG and ARC |
|---------------|------------|--------------------------|
| Lens size: | | H 90 x W 34mm |
| Shade levels: | | 3 and 11 |
| Lens switchir | ng time: | 5/10000s |
| ARC sensors: | | 2 |
| Operating ter | nperature: | -5 to +55°C |
| Power source |): | Li-ion battery and solar |
| Weight: | | 426g |
| Stock | Part | |
| No. | No. | |
| 02517 | WHFS-BKSF | |
| | | |



3 NEW

Filter for use with Welding Helmet - Stock No. 02517

Replacement filter for use with Fixed Shade Auto-Darkening Welding Helmet – Stock No. 02517.

| Stock | Part | |
|-------|--------------|--|
| No. | No. | |
| 04892 | AWHFS-BKSF-F | |

4 NEW

Outside PC Lens for use with Welding Helmet - Stock No. 02517

Replacement outside PC lens for use with Fixed Shade Auto-Darkening Welding Helmet Stock No. 02517. Lens size - H 118 x W 95 x D 1mm

| Stock | Part | |
|-------|---------------|--|
| No. | No. | |
| 04893 | AWHFS-BKSF-LO | |



6

Welding Helmet

EN175 and **CE** approved

- · Injection moulded polypropylene
- Adjustable head band

| Screen size: | | 110 x 90mm |
|----------------------------------|----------------------------------|---|
| Weight: | | 384g |
| Stock No. | Part No. | Description |
| 76714 35266 35267 35268 | W410C W412P W413P W414P | Helmet Shaded 11EW Lens-2 per pack Clear Lens-3 per pack Non Spatter Lens-3 per pack |

5 NEW

Inside PC Lens for use with Welding Helmet - Stock No. 02517

Replacement inside PC Lens for use with Fixed Shade Auto-Darkening Welding Helmet Stock No. 02517. Lens size - H 103.8 x W 47.3 x D 1mm

| Stock No. | Part No. | |
|--------------|---------------|--|
| 04894 | AWHFS-BKSF-LI | |



7

Hand Held Welding Mask

EN175 and **CE** approved

Injection moulded polypropylene

| Screen size: | | 110 x 90mm |
|----------------------------------|----------------------------------|---|
| Weight: | | 342g |
| Stock No. | Part No. | Description |
| 76713 35266 35267 35268 | W400C W412P W413P W414P | Mask Shaded 11EW Lens-2 per pack Clear Lens-3 per pack Non Spatter Lens-3 per pack |

Welding Accessories





FFP2 NR Dust Mask for Welding

Conforms to EN149-FFP2 Specifications

Expert Quality, lightweight disposable dust mask with carbon filter for protection against welding fumes (fine metal particulates), ozone (produced as a by-product of MIG and TIG welding), organic vapours, fine toxic dust fibres and aqueous mists. The easy breathe single exhalation valve, adjustable nose clip and elasticated straps deliver a contoured comfortable fit for the user, which can be worn under a welding mask/helmet if required. Display packed.

| Stock No. | Part No. | Quantity |
|--------------|-------------|----------|
| 82484 | FM26/B | 3 |



Leather Apron

Split suede leather with neck loop, front pockets and waist ties. Packed in polythene bag with display card.

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 09699 | LAPR | |



Large Welders Gauntlets

Manufactured to EN388 4.2.4.4 and EN407 4.1.3.X.4.X Standards

Fully lined leather welding gloves with a total length of 355mm. Display packed.

| Stock No. | Part No. | Size |
|--------------|-------------|------|
| 52336 | LWG/B | 11 |



4

Welding Curtain with Metal Frame, 6 x 6'

Green shaded flame retardant PVC welding curtain to protect from welding spatter and UV and IR radiation. Suitable for use in workshops where the glare from welding and cutting may be a hazard to others. Curtain conforms to BS EN 1598 and it can easily be attached and detached from the black metal frame. Dimensions: 1828 x 1828mm

| Stock | Part | |
|-------|--------|--|
| No. | No. | |
| 28406 | WCE6X6 | |





Spot Weld Cutter Set

Set of two spot weld cutters to drill out welds on body panels. Pilot drill ensures accurate cut. Cutters screw onto hexagon shank and are reversible for extra long life. Shank size 7mm. Display packed.

Contents:

1 x 3/8" Weld cutter 1 x 5/16" Weld cutter

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 57624 | SWC1 | |



MIG Gas Bottle Regulator Disposable Cylinder No Gauge

Regulator suitable for use with disposable gas bottles with Draper gas MIG welders, TIG welders and other manufacturers gas welders. Sold loose.

| Stock | Part | |
|-------|-------|--|
| No. | No. | |
| 44352 | W471D | |



300 Bar Industrial Gas Bottle Regulator with Double Gauge

Large gas bottle regulator with double gauge and bottle connection for CO2. Supplied with tail nut and nipple for attachment of 6mm hose. Fitted with bullnose connector.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 70147 | WREGICO2-2G | |



8

300 Bar Industrial Gas Bottle Regulator with Single Gauge

Large gas bottle regulator with single gauge and bottle connection for CO2. Supplied with tail nut and nipple for attachment of 6mm hose. Fitted with bullnose connector.

| Stock No. | Part No. | |
|--------------|-------------|---|
| 70151 | WREGICO2-1G | , |



9

MIG Gas Bottle Regulator Disposable Cylinder 1 Gauge

Regulator suitable for use with disposable CO2 gas bottles. Fitted with bullnose connector for use with Draper gas MIG welders, TIG welders and other manufacturers' gas welders. Includes single gauge.

| Stock | Part | |
|-------|------------|--|
| No. | No. | |
| 70135 | WREGCO2-1G | |

Welding Accessories



1 25 bar Propane Regulator

Single stage plugged. 3/8" BSP outlet, 5/8" BSP inlet. Display packed.

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 35006 | W700 | |



300 bar Argon Regulator

Single stage with two gauges, one showing output pressure and the other bottle contents. 3/8" BSP outlet, 5/8" BSP inlet connections. Display packed.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 35017 | W703 | |



25 bar Acetylene Regulator

2

Single stage with two gauges, one showing output pressure and the other bottle contents. 3/8" BSP outlet, 5/8" BSP inlet connections. Display packed.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 35008 | W701 | |



5 MIG/TIG Torch Magnetic Stand

For storing MIG and TIG torches. For use with Draper and other manufacturers welding torches. Packed in polybag with display header.

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 08169 | W676 | |



3

300 bar Oxygen Regulator

Single stage with two gauges, one showing output pressure and the other bottle contents. 3/8" BSP outlet, 5/8" BSP inlet connections. Display packed.

| Stock | Part | |
|-------|------|--|
| INU. | No. | |
| 35010 | W702 | |



6

In-Line Flashback Arrestors

Large sintered element coupled with non return valve. 3/8" BSP connectors. Display packed.

| Stock No. | Part No. | For | |
|--------------|-------------|--------|--|
| 35018 | W704 | Fuel | |
| 35019 | W705 | Oxygen | |






Oxyacetylene Welding and Cutting Set (12 Piece)

- Single stage gas regulators with two gauges to show bottle pressure and working pressure
- Two colour coded gas hoses with flashback arrestors and standard 3/8" BSP connectors.
- Welding torch with three lightweight nozzles
- Supplied with sturdy plastic storage case

| Stock | Part |
|-------|--------|
| No. | No. |
| 70155 | WOXSET |

Welding Accessories





Heavy Duty Welding/Cutting Torch Assembly

Designed for sheet metal and the automotive trade. Comprises three separate items: Heavy Duty Shank (Stock No. 35031) which carries oxygen and acetylene and controls gas flow to the Heavy Duty Cutting Attachment (Stock No. 35033) and a Heavy Duty Gas Mixer (Stock No. 35032) for combining oxygen and acetylene which holds welding nozzles (supplied separately). Items are purchased separately to make up combination required. All items are carton packed.

| Stock No. | Part No. | Description |
|--------------|-------------|--------------|
| 35031 | W710 | Shank |
| 35032 | W711 | Gas Mixer |
| 35033 | W712 | C/Attachment |



Welder Cutting Nozzles

For general purpose hand cutting. Carton packed.

| Stock No. | Part No. | Bore | Thickness | For |
|---|--------------------------------------|---|---|---|
| 35042 35044 35049 35050 35052 | W718 W719 W720 W721 W722 | 1/32" 3/64" 1/16" 1/32" 3/64" | 3-6mm 5-12mm 10-75mm 3-6mm 5-12mm | Oxy Acetylene Oxy Acetylene Oxy Acetylene Propane Propane |
| 35054 | W723 | 1/16" | 10-75mm | Propane |





18/90 Cutting Torch

Oxyacetylene/oxygen - propane cutting torch, fitted with mixer nozzles and flame retardant handle. Display

| Stock | Part | |
|-------|--------|--|
| No. | No. | |
| 85937 | W733/A | |



Oxy Acetylene Swaged Welding Nozzles

A selection of used with traditional shank or welding

| Stock No. | Part No. | Size | Thick- ness | Level | For |
|--------------|-------------|-------|----------------|---------------|---------------|
| 35035 | W713 | No.2 | 1.2mm | Heavy Duty | Oxy Acetylene |
| 35036 | W714 | No.3 | 2.0mm | Heavy Duty | Oxy Acetylene |
| 35037 | W715 | No.5 | 2.6mm | Heavy Duty | Oxy Acetylene |
| 35038 | W716 | No.7 | 3.2mm | Heavy Duty | Oxy Acetylene |
| 35040 | W717 | No.10 | 4.0mm | Heavy Duty | Oxy Acetylene |





Acetylene/Oxygen/Propane Hoses

Manufactured in accordance with BS ISO3821, 730 and 1256

Fitted with swivel nut connectors at either end. Display packed.

| Stock No. | Part No. | For | Size | |
|--------------|-------------|-----------|------------|--|
| 05515 | W738 | Acetylene | 10m x 6mm | |
| 35023 | W706 | Acetylene | 10m x 10mm | |
| 05516 | W737 | Oxygen | 10m x 6mm | |
| 35026 | W708 | Oxygen | 10m x 10mm | |
| 35028 | W709 | Propane | 10m x 10mm | |



Welding Nozzle Cleaner

A selection of stainless steel nozzle files for cleaning holes in welding and cutting nozzles. Packed in case. Display packed.

| Stock | Part | |
|-------|------|--|
| No. | No. | |
| 35105 | W732 | |



Flint Gun

For the lighting of oxy acetylene for welding or brazing. Display packed.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 35108 | W735 | |



Flint Cup Lighter

For the lighting of oxy acetylene for welding or brazing in draughty conditions. The cup shields the spark from extinguishing. Display packed.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 35107 | W734 | |



Gas Bottle Key

For general use on gas equipment and 20mm or 27mm open end. Can be used on 6.4mm square drive cylinder valves.

| Stock No. | Part No. | |
|--------------|-------------|--|
| 35109 | W736 | |